



# Sigma Lubricants



## Brake Fluid Dot-4

Sigma Brake Fluid Dot-4 is a high performance polyglycol type Brake Fluid (Dot-4) designed to use in brake and clutch systems. It optimizes the benefits of superior boiling point and high vapour lock temperature through its service life.

Sigma Brake Fluid Dot-4 is compatible with all metals and rubber seals typically used in automotive braking systems. It is suitable for disc, drum and anti skid ABS braking and electronic stability control systems used in high performance vehicles with high thermal load around the braking systems.

Conforms to Federal Motor Vehicle Safety Standard No. 116. Meets SAE J1703 and W-B-680 Specifications. Initial Boiling Temperature and Melting Temperature Range 230°C

### BENEFITS

- Formulated from polyglycol with lubricity additives and corrosion inhibitors
- High level system protection
- Excellent lubricating properties
- Correct fluidity and kinematics viscosity
- Proper anti oxidants, metal deactivator and corrosion inhibitors.



Data Sheet

Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Sigma Oil Industries Limited warrants only that its products meet the specification which is set for them and specially DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.